

Optimal Path in Wireless Ad hoc Network (WANET) and Mobile Ad hoc Network (MANET)

Dr. C Mohammed Gulzar, Associate Professor & HoD, CSE, Dr. K.V.Subba Reddy Institute of Technology, Kurnool.

K.Samson Paul, Assistant Professor, CSE, Dr. K.V.Subba Reddy Institute of Technology, Kurnool.

Bushra Tahseen, Assistant Professor, CSE, Dr. K.V.Subba Reddy Institute of Technology, Kurnool.

Article Info

Volume 82

Page Number: 1794 - 1798

Publication Issue:

January-February 2020

Abstract

We studied the way of minimizing a grand total of all convex objective functions, where the attributes of the objective functions are available to different nodes of a cellular network and the cellular nodes are allowed to only communicate with their nearest neighbors. This paper deals with different evolutionary methods, provided to fix the best optimized routes for data communication for peer to peer in mobile communication networks. This differential approach for global multi-objective network simulation, in regards to perform with publishing the prime affordable path in mobile networks. This prototype holds the affordable cost to go for the minimal cost for the path. The multiobjective optimization algorithm is applied as a diagnosis tool for checksum based encryption in data transmission. In the end test results passed by proposed algorithm fulfills the genuineness, in regards to traditional algorithms such as Particle Swarm Optimization and Genetic Algorithm.

Article History

Article Received: 14 March 2019

Revised: 27 May 2019

Accepted: 16 October 2019

Publication: 07 January 2020

Keywords— *convex objective functions; checksum; encryption; particle swarm optimization; genetic algorithm; multiobjective optimization; MANNET; Destination Sequenced Distance Vector (DSDV) protocol, Distance vector (DV) protocol and Fisheye State Routing (FSR) protocol; proactive, reactive and hybrid protocols; WANNET*

I. INTRODUCTION

In MANNET Ad-hoc based cellular networks, the roaming mechanism of packets have a distinct goal on the transaction of peer to peer nodes. There are several adhoc-based cellular network algorithms which find their shortest path: the Dijkstra's Shortest Path First algorithm which is based on greedy technique and time complexity is $O(V\log V)$ (with the use of Fibonacci heap). Again the Breadth First Search (BFS) algorithm traverses a graph in a breadth ward motion and uses a queue to remember to get the next vertex to start a search, when a dead end occurs in any iteration. Also The Bellman-Ford algorithm is an algorithm that computes shortest paths from a single source vertex to all of the other vertices in a weighted digraph. It is slower than Dijkstra's algorithm for the same problem, but more versatile, as it is capable of handling graphs in which some of the edge weights are negative numbers. etc. Quasi-Static Detection Algorithm considering the fact that a generic mobile device can obtain the identification of QS instants is a classical binary subjected to various types of motions and that the pattern of the hypothesis testing

problem where the two possible hypotheses can be so defined. the above algorithms produces unexpectedly high computational complexities for upcoming network topologies given below. Mobile cellular multi hop network is deployed in wireless sensory network with a signal-to-noise ratio(SNR) that based on transmission range of adhoc nodes which prepares routing table for transmission of data for peer to peer. Almost all nodes of an ad hoc network take part in maintenance and discovery of routes in the network. The routing protocols proposed for wired networks cannot be used for ad hoc or mobile network networks due to network mobility. There are three broad categories of mobile ad hoc network routing protocols : **proactive, reactive and hybrid** protocols. In proactive routing protocol, each node of the network maintains a single or multiple routing tables that are regularly updated. Each node will send a broadcasting message to all the other nodes in the network in order to detect the changes in their network topology. Example: Destination Sequenced Distance Vector (DSDV) protocol, Distance vector (DV) protocol and Fisheye State Routing (FSR) protocol

On the other side, in Reactive Protocol, each network node discovers its route to destination. This optimization know-how makes the energy emission and adds reliability to the search path. A wireless sensor network is a group of specialized transducers with a communications infrastructure for monitoring and recording conditions at diverse locations. Commonly monitored parameters are temperature, humidity, pressure, wind direction and speed, illumination intensity, vibration intensity, sound intensity, power-line voltage, chemical concentrations, pollutant levels and vital body functions. It is having extra throughput because of infrastructure communication, the mobile devices area unit carried by humans and area unit used creates the node failure detection in mobile wireless networks which is extremely difficult as a result of the topology will be extremely dynamic thanks to node movements.

Therefore the feasibility study claims that the area unit designed for static ad-hoc networks isn't applicable. Second, the network seems to be disconnected. Therefore, the applied approaches that consider network property have restricted pertinence. Third, the restricted on demand resources claim for the node failure detection. A heartbeat protocol is generally used to negotiate and monitor the availability of a resource, such as a floating IP address. Typically when a heartbeat starts on a machine, it will perform an election process with other machines on the heartbeat network to determine which machine, if any, owns the resource. A wireless ad hoc network (WANET) or Mobile ad hoc network (MANET) is a decentralized type of wireless network. The network is ad hoc because it does not rely on a pre-existing infrastructure, such as routers in wired networks or access points in managed (infrastructure) wireless networks.

The wireless measurement nodes communicate with a central gateway using a protocol based on IEEE 802.15.4 to offer mesh routing capabilities that extend network distance and reliability. NI WSN systems support lower data rates to preserve power, are easily programmed using I/O variables. These devices are intended for longer term, slower speed applications in which the mobile user might be interested in monitoring the wireless measurement nodes communicate with a central gateway using a protocol based on IEEE 802.15.4 to offer mesh routing capabilities that extend network distance and reliability. NI WSN systems support lower data rates to preserve power, are easily programmed using I/O variables. These devices are intended for longer term, slower speed applications in which you might be interested in monitoring. With this type of protocol the choice of proactive and of reactive routing depends on the hierarchic level in which a node resides. The routing is initially established with some proactively prospected routes and then serves the demand from additionally activated nodes through reactive flooding on the lower levels.

However it suffers from inherent ambiguities—when a node A stops hearing heartbeat messages from another node B, A cannot conclude that B has failings a result of the shortage of heartbeat messages could be caused by node B having quarantined of vary rather than node failure.

Simulation results the bottleneck of each protocol gets through the success of high precipitation rates, but low segmentation rates which incurred the lowest communication overhead. Compared to the use of Destination Sequenced Distance Vector (DSDV) protocol, Distance vector (DV) protocol and Fisheye State Routing (FSR) protocol, our approach could have got accurate detection rates which is considerably very lower communication overhead. The rest of the section is organized as follows. Section two describes inter-connection over connected work. Section three describes the test dataset which is nothing but the matter setting. Section four presents the statistics. Section five presents our faulty node detections and avoidances. Section six evaluates the performance of technical feasibility schemes. In conclusion, Section seven the paper presents future scenario.

II. PROBLEM DEFINITION

Somehow current journals on node detection in wireless cellular networks estimate less network traffic. Many journals prove that the heartbeat established techniques which can be often used in distributed computing. Hence the Probe-and-ACK situated procedures happens in a real time situation with Sensory Nodes with a vital reveal to send probe messages to different nodes. If a node does not reply in between a timeout interval, the critical screen regards to the sensory node has failed. Heartbeat founded methods vary from Probe and- ACK established techniques in order to reduce the latitude and longitude factor of cohesive segment to decrease the quantity of messages. A few current studies established protocols, where a node, upon receiving a bad packet of gossip message on critical node failure scenario, merges its information with the knowledge received, after which proclaims the mixed knowledge. An original probing packet of probe-and-ACK, heartbeat and gossip founded tactics is that they are best relevant to networks which might be linked. Furthermore, they result in a big amount of community-wide monitoring traffic. In distinction, our method simplest generates the localized FIFO (First In First Out) Queue circular in a round robin base monitoring traffic and is applicable to only disconnected networks. The scheme in uses localized monitoring, chatting in a disconnected way. Our method takes account of node mobility. To the first-rate of our potential, our technique is

the first that takes expertise of area know-how to notice node screw ups in all cell networks. As different associated work, To be taught of detects pathological intermittence assuming that it follows a two-state Markov mannequin theorem, which may not preserve in apply due to the ambience, throughput and the threshold of localizes network interface screw ups with an awfully high overhead: it uses periodic pings to receive finish-to-finish failure information between every pair of nodes, uses periodic trace routes to acquire the present network topology, after which transmits the failure.

III. SYSTEM DESIGN




Fig.1.MANET [8] with 20 nodes

Existing System

In this section we compare the performance of the proposed NN fair classifier method with classical methods such as DGD in the accelerated version of DGD in [14]. For the Accelerated Version of DGD method, we propose that the parameters and the momentum coefficients are constant as in the case for the centralized accelerated gradient descent. This makes the comparison between Acc. DGD and NN fair, since our motto is to compare their performances in solving the penalized objective function. Moreover, we consider the convergence paths of the distributed. ADMM i.e. a mobile ad hoc network (ADMM)[18] is generally defined as a network that has many free or autonomous nodes, often composed of mobile devices or other mobile pieces, that can arrange themselves in various ways and operate without strict top-down network administration. Security in Ad hoc networks are a new wireless networking paradigm for mobile hosts. The military tactical and other security-sensitive operations are the main applications of ad hoc networks, although there is a trend to adopt ad hoc networks for commercial uses due to their unique properties and that is the exact first order method EXTRA in [16]. Although EXTRA used to operate in the primary domain, it has been shown that it can be interpreted as a

saddle-point method [27]. Thus, we consider EXTRA in the category of dual methods which has a linear convergence rate as DAD-MM. A few current studies undertake gossip established protocols, where a failure node, upon receiving a gossip message on node failure understanding, merges its information with the knowledge received, after which proclaims the mixed knowledge. An original main issue of Probe-and-ACK, heartbeats and gossip founded messages shows that they are the best relevant to the networks which might be linked with our method which generates localized monitoring traffic and is applicable to both related and disconnected networks. The scheme in uses localized monitoring. It is, however, now not compatible for cell networks on the grounds that it does not do not forget that failure to hear from a node probably due to node mobility instead of node failure. Our method takes account of node mobility. To the first-rate of our potential, our technique is the very first method that takes expertise of ad-hoc mobile area network(MANET) to know-how to notice the faulty node screw ups in cellular networks. As single-hop and multi-hop based MANNET ad-hoc network, assuming that it follows a two-state Markov Mannequin, which is a Markov model is a stochastic method for randomly changing systems where it is assumed that future states do not depend on past states. This will be applied for localization network interface screw ups with an awfully high overhead: it uses periodic pings to receive finish-to-finish failure information between every pair of nodes, uses periodic trace routes to acquire the present network topology, after which transmits the failure.

Disadvantages

1. No Network Data packet takes more time to arrive from source to destination.
2. No information about the receiver i.e. data reached successfully or not.

Proposed system:

On this part, we first use an illustrating example to inspire our approach, after which gift a core constructing block of our strategy. On the finish, we present a higher bound of failure detection fee when using our procedure. We use the instance to inspire our method. In this example, for simplicity, we anticipate no packet losses and that every node has the same round transmission range. At time t , all the nodes are alive, and node $N1$ can heartbeat messages from $N2$ and $N3$. At time t , node $N2$ fails and $N3$ moves out of $N1$'s transmission range fig-2. Via localized monitoring, $N1$ best knows that it could possibly now not hear from $N2$ and $N3$, however does no longer understand whether the

shortage of messages is because of node failure or node moving out of the transmission range. Place estimation is beneficial to unravel this ambiguity: headquartered on region estimation, N1 obtains the probability that N2 is inside its transmission range, finds that the chance is excessive, and for this reason conjectures that the absence of messages from N2 is likely as a result of N2's failure; in a similar way, N1 obtains the likelihood that N3 is within its transmission range, finds that the probability is low, and hence conjectures that the absence of messages from N3 is likely considering N3 is out of the transmission variety. The above selection will also be multiplied via node collaboration. For example, N1 can broadcast an inquiry about N2 to its one-hop neighbors at time $t \geq 1$, and use the response from N4 to either affirm or correct its conjecture about N2. The above example indicates that it's primary to systematically mix localized monitoring, vicinity estimation and node collaboration, which is the most important of our strategy.

Advantages

1. With Proposed system it will transfer the data from source to destination fast compare to previous system.
2. Whenever user will connect to a network and disconnect from network, each and every record should be maintain.
3. To connect the proposed NN method with the classic Newton's method, we first study the difference between these methods. In particular, the following lemma shows that the convergence of the norm of the weighted gradient $\frac{1}{2} \sum_{t=1}^{t-1} \mathbf{g}_t$ in NN-K is akin to the convergence of Newton's method with constant step size.

IV. PROPOSED ALGORITHM:

1. Binary Newton Network Scheme
 - Sending Query Data to Network.
 - Processing the Data in Network.
 - Receiving Query Data to Network.
 - Showing the output data Segment from Nodes.
2. Non-Binary Newton Network Scheme
 - Sending Query to the Newton Network.
 - Processing the Data inside the Network.
 - Receiving Query to the Newton Network.
 - Output Data Segment Model In the Main Node.

Algorithm for optimal path DEO

1. Set the control parameters
F=1 and Cr=0.8
2. Initialize nodes of MANET as Population that is (a_1, a_2, \dots, a_n)
3. Applying route encoding scheme
4. Initialize the solution for each candidate nodes
5. ITR=1
6. While route_fitness < route_max_fitness
7. Mutation: Generate donor vector through equation (5) to explore all alternative routes
8. Crossover: Generate trial vector through (6) to explore partial routes
9. Selection: Compare trial vector and target vector to select the best vector by equation (7)
- 10 ITR=ITR+1
11. End

Algorithm 1: Network Newton-K method at node i .

Require: Initial iterate $x_{i,0}$. Weights w_{ij} . Penalty coefficient α .

- 1: B matrix blocks: $B_{ii} = (1 - w_{ii})\mathbf{I}$ and $B_{ij} = w_{ij}\mathbf{I}$
 - 2: for $t = 0, 1, 2, \dots$ do
 - 3: D matrix block: $D_{ii,t} = \alpha \nabla^2 f_i(x_{i,t}) + 2(1 - w_{ii})\mathbf{I}$
 - 4: Exchange iterates $x_{i,t}$ with neighbors $j \in \mathcal{N}_i$.
 - 5: Gradient: $\mathbf{g}_{i,t} = (1 - w_{ii})x_{i,t} - \sum_{j \in \mathcal{N}_i} w_{ij}x_{j,t} + \alpha \nabla f_i(x_{i,t})$
 - 6: Compute NN-0 descent direction $d_{i,t}^{(0)} = -D_{ii,t}^{-1}\mathbf{g}_{i,t}$
 - 7: for $k = 0, \dots, K - 1$ do
 - 8: Exchange elements $d_{i,t}^{(k)}$ of the NN-k step with neighbors
 - 9: NN-(k + 1) step: $d_{i,t}^{(k+1)} = D_{ii,t}^{-1}[\sum_{j \in \mathcal{N}_i, j \neq i} B_{ij}d_{j,t}^{(k)} - \mathbf{g}_{i,t}]$
 - 10: end for
 - 11: Update local iterate: $x_{i,t+1} = x_{i,t} + \epsilon d_{i,t}^{(K)}$.
 - 12: end for
-

IV. CONCLUSION

In this paper, we tend to be store a data in newton network probabilistic approach and designed 2 node failure detection schemes that mix localized watching, location estimation and node collaboration for mobile wireless networks. Intensive simulation results demonstrate that our schemes reach high failure detection rates, low false positive rates, and low communication overhead. We tend to additional incontestable the tradeoffs of the binary and non-binary feedback schemes. We developed the network Newton method as an approximate Newton method for solving consensus optimization problems. The algorithm builds on a reinterpretation of distributed gradient descent as a penalty method and relies on an approximation of the Newton step of the corresponding penalized objective function. To approximate the Newton direction we truncate the Taylor series of the exact Newton step. This leads to a family of methods defined by the number K of Taylor series terms kept in the approximation. When we keep K terms of the Taylor series, the method is called NN-K and can be

implemented through the aggregation of information in K-hop neighborhoods. This paper compares the results based on the suggested encoding scheme for all three evolutionary algorithms for finding optimal path in mobile ad-hoc networks. The quality of solution achieved by DEO in all three test set are better than PSO and GA. DEO converges faster than the other two Our approach depends on location estimation and therefore the usage of heartbeat messages for nodes to observe one another. Therefore, it doesn't work once location info isn't on the market or there's communication blackouts (e.g., because of weather conditions). Developing effective approaches for those eventualities is left as future work.

REFERENCES

1. Storn R, Price K., "Differential evolution- a simple and efficient adaptive scheme for global optimization over continuous spaces, 1995; Technical Report TR-95-012. ICSI.
2. H. Yetgin, K.T. K. Cheung, and L. Hanzo, "Multi-objective routing optimization using evolutionary algorithms," in Proceeding of the IEEE Wireless Communication and Networking Conference (WCNC' 12), pp. 3030-3034, IEEE, Shanghai, China, April 2012.
3. Stephen Gundry, Jianmin Zou, Janusz Kusyk, Cem Safak Sahin and M.Umit Uyar, Markov chain model for differential based topology control in MANETs. Sarnoff Symposium (SARNOFF), 2012 35th IEEE
4. Stephen Gundry, Jianmin Zou, Janusz Kusyk, M. Umit Uyar , Cem Safak Sahin and, Fault tolerance bio-inspired topology control mechanism for autonomous mobile node distribution in MANETS, MILITARY COMMUNICATIONS CONFERENCE, 2012 - MILCOM 2012.
5. Stephen Gundry, Janusz Kusyk, Jianmin Zou, Cem Safak Sahin and M.Umit Uyar, Differential Evolution based fault tolerant topology control in MANETs. Military Communications Conference, MILCOM 2013 - 2013 IEEE.
6. U.K. Chakraborty, S. K. Das, T. E. Abbott, "Clustering in mobile ad hoc networks with differential evolution," Evolutionary Computation (CEC), 2011 IEEE Congress.
7. Anjum A. Mohammed, Gihan Nagib, "Optimal routing in ad-hoc network using genetic algorithm," Int. J. Advanced Networking and Applications Volume:03, Issues:05, Pages:1323-1328 (2012).
8. Chang Wook and R.S. Ramakrishna, "A genetic algorithm for shortest path routing problem and the sizing of populations", IEEE transaction on evolutionary computation 6.6 (2002): 566-579.
9. Ren Jingjua, Jiuwei Wang, Yulong Xu, Li Cao, "Applying differential evolution algorithm to deal with optimal path issues in wireless sensor networks", Mechatronics and Automation (ICMA), wireless sensor networks", Mechatronics and Automation (ICMA), 2015 IEEE International Conference on ,2015.
10. Y. Hao, "Wireless sensor network path optimization based on particle swarm algorithm," Computer Engineering, 36(4):91-96, 2010.

AUTHORS DETAILS:



1. Dr. C. Mohammed Gulzar is an efficient teacher & HOD, He is working as an Associate Professor in the Department of C.S.E, Dr. K. V. Subba Reddy Institute of Technology, Kurnool. He has 14 years of teaching experience. He has supported many students to publish many papers in both National & International Journals. His area of Interest includes Mobile Adhoc Networks and Cloud computing.



2. Mr. K. Samson Paul is an efficient teacher , He is working as an Assistant Professor in the Department of C.S.E, Dr. K. V. Subba Reddy Institute of Technology, Kurnool. He has 9 years of teaching experience. He has supported many students to publish many papers in both National & International Journals. His area of Interest includes Mobile Adhoc Networks and Artificial Intelligence.

3. Mrs. Bushra Tahseen, working as an Assistant Professor in Department of C.S.E at Dr. K. V. Subba Reddy Institute of Technology, Kurnool. Pursuing her Ph.D from Rayalaseema University, Kurnool. She has 15 years of teaching experience. She has published many papers in both National & International Journals. Her area of Interest includes Data mining, Fuzzy logic and networking.